

224 Vassar Street, Suite A, Reno, NV 89502 * PHONE: (775) 324-4044 * FAX: (775) 324-4635 E-MAIL: andrew@satoenviro.com

May 17, 2007

Mr. Brett Whitford AMEC Earth & Environmental 780 Vista Boulevard, Suite 100 Sparks, Nevada 89434-6656

Regarding: Report for AMEC Proposal No. PN07-2-2; Environmental Protection Agency (EPA),

National Emission Standard for Hazardous Air Pollutants (NESHAPS), Limited Supplemental Asbestos Containing Material (ACM) Survey Prior to Future Demolition of the Gabbs Old Recreation Hall, Located at 531 Avenue E, Gabbs, NV.

Sato Environmental Project #210-01

Dear Mr. Whitford,

Sato Environmental has completed the site inspection and bulk sampling supplemental to the sampling performed previously by Ninyo & Moore to identify ACM during a Phase I Environmental Site Assessment of the property comprising the Gabbs Old Recreation Hall in Gabbs, NV.

This letter documents the ACM that was identified based on the results previously provided by Ninyo & Moore (refer to samples number B-01 –B-25) plus the results of 28 supplemental samples collected by Sato Environmental (refer to samples number B-2-B01 –B-2-B28) and analyzed by others.

ACMs Identified During Ninyo & Moore and Sato Environmental Surveys

The type of material, the location of the ACM identified, the percentage of asbestos content, and the form of asbestos identified in the materials analyzed are listed in the table on the following page.

Sato Environmental Consultants, Inc. (SECI) May 17, 2007 AMEC Proposal No. PN07-2-2

Supplemental ACM Demolition Survey

	ACM Identified in the Gab	e Gabbs, Old Recreation Hall, 531 Avenue E, Gabbs, NV.	ion Hall,	531 Ave	nue E,	Gabbs, NV.
	Ninyo & Moore	ACM Sample Results and Field Data	nd Field Da		t Dated J	Report Dated July 8, 2003
Sample Number	Material	Location	Quantity	Condition	Friable	Asbestos Type and Content
B-006	Joint Compound on Sheetrock	Entrance, West Wall	N/A	Fair	No	2% Chrysotile Asbestos
B-011	9" X 9" Vinyl Floor Tile (Gray)	Women's Restroom	38 sf	Damaged	No	5% Chrysotile Asbestos
B-023	Roof Mastic and Silver Coating	Roof over Women's Restroom	N/A	Good	No	Silver Coating: 3%; Mastic 10% Chry
B-024	Roof Tar (Beige & White)	Roof over Meeting Hall	N/A	Fair	No	10% Chrysotile Asbestos
B-025	Roof Tar (Beige & White)	Roof over Meeting Hall	N/A	Good	No	10% Chrysotile Asbestos
	Sato Environmental Consultants, Inc.	Inc. ACM Sample Results and Field Data	Results and	Field Data	Report	Report Dated May 17, 2007
Sample Number	Material	Location	Quantity	Condition	Fri.	Asbestos Type and Content
B-2-B04	9" X 9" Floor Tile & Mastic (Grey)	Kitchen (located in Basement)	300 sf	Fair	No	Floor Tile: 2-5%; Mastic 10-20% Chry
B-2-B05	Floor Tile Mastic (on concrete)	Basement Area W. of Kitchen	300 sf	Damaged	No	20-30% Chrysotile Asbestos
B-2-B06	Joint Compound, Plaster & Skim Coat on Beams	Basement Area W. of Kitchen	80 sf	Damaged	Yes	2-5% Chrysotile
B-2-B18	9" X 9" Floor Tile/Sheet Flooring (without the typical ACM felt backing)	Northeast Hall and Rooms of First Floor of Structure	350 sf	Damaged	No	Floor tile Portion 2-5% Chrysotile

* Please Note: Non-Friable Joint Compound on sheetrock, Flooring Mastic (unless on concrete) and Roofing Materials in Fair to Good condition could typically be left in place during demolition of a structure in accordance with the NESHAPS.

Sato Environmental Consultants, Inc. (SECI) May 17, 2007 AMEC Proposal No. PN07-2-2 Supplemental ACM Demolition Survey

All of the materials identified as ACM and quantified in the preceding table require abatement by a qualified, and insured Abatement Contractor that is licensed in the State of Nevada prior to being disturbed during demolition of the structure.

Materials identified as ACM should only be disturbed by personnel having asbestos specific training for the type of ACM as well as the kind of contact that could create a disturbance (asbestos fiber release), such as, Housekeeping, Maintenance, Renovation, or Demolition Operations.

Regualtory Compliance

Excerpt from the EPA, NESHAPs Regulation Applicable to Demolition of the Subject Structure: DEMOLITION PRACTICES AND NONFRIABLE MATERIALS (A Limited Introduction)
INTRODUCTION

EPA revised the asbestos NESHAP regulations on November 20, 1990 (see 40 CFR Part 61 Subpart M). Although the NESHAP has not been revised to alter its applicability to friable and nonfriable asbestos-containing materials (ACM), nonfriable asbestos materials are now classified as either Category I or Category II material.

Category I material is defined as asbestos-containing resilient floor covering, asphalt roofing products, packings and gaskets. Asbestos-containing mastic is also considered a Category I material (EPA determination - April 9, 1991). Category II material is defined as all remaining types of non-friable ACM not included in Category I that, when dry, cannot be crumbled, pulverized, or reduced to powder by hand pressure. Nonfriable asbestos-cement products such as transite are an example of Category II material.

The asbestos NESHAP specifies that Category I materials which are not in poor condition and not friable prior to demolition do not have to be removed, except where demolition will be by intentional burning. However, regulated asbestos-containing materials (RACM) and Category II materials that have a high probability of being crumbled, pulverized, or reduced to powder as part of demolition must be removed before demolition begins.

The limited amount of Floor Tile/Sheet Flooring in the Northeast Areas of the first floor are deteriorated and would have a high probability of being rendered Friable during demolition and must be abated prior to demolition. The Drywall Joint Compound and Plaster & Skim Coat on Beams in the Basement are potentially Friable and Categorized as Regulated Asbestos Containing Material (RACM). The Floor Tile & Mastic are considered Category 1 Non-Friable Asbestos according to the EPA, NESHAPs regulation. The EPA, NESHAP regulation that governs demolition work is enforced by the EPA Region IX Office in San Francisco. To comply with the NESHAP the Friable (can be reduced to dust with hand pressure when dry) ACMs or Non-Friable ACMs that could be rendered friable during demolition must be removed by a licensed abatement contractor prior to demolition of a building or structure.

Sato Environmental Consultants, Inc. (SECI) May 17, 2007 AMEC Proposal No. PN07-2-2 Supplemental ACM Demolition Survey

While the EPA NESHAP regulation does not necessarily apply to ACMs identified when the material remains non-friable, other requirements in Federal Occupational Safety and Health Administration (OSHA) and State Occupational Safety and Health Enforcement Section (OSHES) asbestos regulations must be followed. OSHA and OSHES consider removal of the Non-Friable ACMs identified as Class two (2) Asbestos Abatement work. Various requirements from the Federal OSHA and State OSHES asbestos regulations apply regardless of friability if the material will be disturbed. A licensed abatement contractor should be utilized to remove any ACM that must be removed prior to demolition which applies to all of the ACMs in the subject structures with the exception of Joint Compound on Sheetrock and non-friable roofing materials and flooring mastics that are not on concrete where demolition equipment would abrade the flooring mastics.

EPA could allow the Floor Tile and Mastic to remain in place during demolition unless the concrete is going to be recycled, however, OSHA and EPA do not allow for rendering non-friable materials friable during demolition. Demolition of the structure would inevitably impact the Floor Tile and the Mastic in the basement in a manner that would render at least a portion of the materials friable. Roofing material in good condition could typically remain for demolition.

At the time of the survey the building was vacated and destructive sampling could be performed. All of the insulation observed in the structure was cellulose or fiberglass and there was no insulation observed on any of the water piping in or beneath the structure.

During the inspection and sampling processes, Sato Environmental brought the survey of the structure into compliance with specific guidelines provided by the EPA and OSHA regarding the number of samples that must be collected based on the material type, condition, friability, and quantity. Some materials tend to contain asbestos in limited amounts or areas of the material due to inconsistent mixing of asbestos into the materials, for example, troweled-on; sprayed-on texturing materials and drywall joint compound could reveal negative results for ACM in areas sampled and have adjacent areas not sampled that do contain asbestos.

Some suspect materials may remain undiscovered inside walls, above ceilings or in hidden interstitial spaces. If any suspect ACM not addressed in this report is discovered during the course of future demolition work the material must be sampled by a licensed Asbestos Inspector and analyzed for asbestos content by an accredited laboratory prior to disturbing the material. This report applies only to the materials listed in the lab analytical reports and in areas that were accessible and as defined in the field data for the surveys the report was based upon.

The laboratory analytical reports, sample data sheets, and sample location sketches describe general locations of samples collected and are attached for reference.

Suspect ACMs that were sampled during the survey and determined <u>Not</u> to be Asbestos Containing Material include: Roofing Felts beneath Exterior Siding, Rolled Roofing, Roofing Felts on roofs, Asphalt Roof Shingles, Drywall Tape, Sheetrock, Wall Texture on Sheetrock, 1" X 1" Acoustic Ceiling Tiles, Ceiling Insulation, Wire Insulation, Wall Fiber-Board, Joint Compound on Fiber-Board and Asphalt Felt Paper between Hardwood Flooring & Sub-Flooring in the Theater.

Following Abatement of Regulated ACMs in Nevada, a NV, OSHA, Air Clearance Sampling and Analysis protocol must be met prior to Re-Occupancy of a building. The areas that presently would require abatement would not require Air Sampling Prior to Demolition of the Structure if the structure could be demolished without re-occupancy of the structure by Non-Abatement Personnel. Demolition of the structure by the same contractor that performs the abatement or by a different Demolition Contractor if Demolition is Performed Immediately Following the Abatement could eliminate the necessity of Non-Abatement Personnel entering the building which could eliminate the requirement for Clearance Air Sampling and Laboratory analysis of Samples which could save the Owner several thousand dollars.

Laboratories Location and Analytical Method

The bulk samples of suspect ACM collected by Sato Environmental were analyzed for asbestos content by AMEC (an accredited analytical laboratory) located in Tempe, AZ. The bulk sample analysis was performed in accordance with EPA Method 600/R-93/116 for the determination of asbestos in bulk building materials using dispersion staining and a visual area estimation technique.

Please contact Andrew Sato at (775) 324-4044 if you have any questions regarding this report.

Andrew D. Sato


John West

Licensed Asbestos Consultant Nevada License Number IJPM0048

California Asbestos Certification (CAC) #97-2286

Attachments:

- 1) Sketch of the structure surveyed showing sampling locations for ACM.
- 2) Laboratory analytical results of AMEC's PLM Analysis.



Gabbs Recreation Center
531 Avenue "E", Gabbs, Nevada
O-----ACM Sampling Locations

Summary of PLM Analysis

AMEC Earth & Environmental 1405 W. Auto Drive Tempe, AZ 85284 (480) 940-2320 (480) 785-0970 Fax TDSHS# 30-0308

NVLAP ID: 200444-0

Project ID 7-417-000764

Project Name 7-417-000764

Building Name 7-417-000764_4/25

Sample Number: B-Sample Type: Joint C	2-B01 Compound	Lab II	D: 45908		ACM? □
	er Detail		17:2L	%	
Layer # 1 White	Flakes	Point	<u>Fiber</u>	70	
Layer w winter	2 241102		None	0	
Layer # 2 Green	Flakes	Paint			
			None	0	
Layer# 3 White	Powder	Texture			
•			Cellulose	5-10	
			Glass fiber	1-2	
Layer # 4 Brown	Fibrous	Backing			
			Cellulose	80-90	
Layer # 5 White	Clumpy	Wall board			
			Cellulose	5-10	
Layer # 6 Brown	Fibrous	Backing	•		
			Cellulose	70-80	
Non-Fibrous Components;	Powder, binder				
Sample Comments:					

	ject Name 17-000764		Building 7-41'	Name 7-000764_4/2	5
Sample Number: B-2	-B02	Lab IL): 45909		ACM? □
Sample Type: Plaster	Wall Texture				
<u>Layer</u>	r Detail		<u>Fiber</u>	%	
Layer# 1 White	Flakes	Paint			
			None	0	
Layer # 2 Green	Flakes	Paint			
			None	0	
Layer # 3 White	Powder	Texture			
			Cellulose	2-5	
Layer # 4 Brown	Fibrous	Backing	G 11 1	የለ ሰስ	
	m 1 12 de-		Cellulose	80-90	
Non-Fibrous Components;	Powder, binder				
Sample Comments:					
Sample Number: B-2	E-B03	Lab II	D: 45910		ACM?
Sample Type: Plaster	Wall Texture				
Laye	r Detail		<u>Fiber</u>	%	
Layer # 1 White	Flakes	Paint			
			None	0	
Layer # 2 Green	Flakes	Paint			
			None	0	
Layer # 3 Brown	Fibrous	Backing			
			Cellulose	8090	
Layer# 4 White	Clumpy	Wall board		£ 10	
			Cellulose	5-10	
Non-Fibrous Components;	Powder, binder				
Sample Comments:					

Project ID Project Name 7-417-000764 7-417-000764			Building 7-41	Name 7-000764_4/	25
Sample Number: 1	3-2-B04	Lab IL	e: 45911		ACM? ☑
Sample Type: Floo	or Tile and Mastic				
La	yer Detail		<u>Fiber</u>	%	
Layer # 1 Gray	Brittle	Floor tile			
			Cellulose	1-2	
			Chrysotile	2-5	
Layer# 2 Black	Sticky	Mastic			
			Chrysotile	10-20	
Non-Fibrous Components;	Vinyl, binder				
Sample Comments:					
Sample Number: 1	3-2-B05	Lab ID	÷ 45912		ACM? ☑
Sample Type: Flor	or Tile and Mastic			-	
La	iver Detail		Fiber	%	
Layer # 1 Black	Clumpy	Floor tile mastic		,5	
			Cellulose	1-2	
			Chrysotile	20-30	
Non-Fibrous Components;	Vinyl, binder		•		
Sample Comments:					
Sample Number: I	R-2-R06	Lab ID	: 45928		ACM? ☑
	il Compound				110112.
•	iyer Detail		<u>Fiber</u>	%	
Layer # 1 White	Powder	Joint compound	<u>rwer</u>	70	
		•	None	0	
Layer # 2 Beige	Flakes	Skim coat			
•			Chrysotile	2-5	
Layer# 3 White	Powder	Plaster			
			Chrysotile	2-5	
Non-Fibrous Components;	Powder, binder				
Sample Comments:					
Friday, May 04 2007			AMEC Repo		

.___.

	Project Name 1-417-000764	1	Buildin 7-4	g <i>Name</i> 17-000764_4/2	25
Sample Number: B	-2-B07	Lab II	D: 45943		ACM? □
Sample Type: Plast	ter Ceiling				
<u>Lay</u> Layer# 1 Beige	y <i>er Detail</i> Flakes	Paint	<u>Fiber</u>	%	
-			None	0	
Layer # 2 Beige	Granular	Skim coat	None	0	
Layer# 3 White	Granular	Plaster			
			Cellulose	1-2	
Non-Fibraus Components; Sample Comments:	Cementitious	s Material			
Sample Number: B	-2-B08	Lab II	D: 45944		ACM? □
Sample Type: Acou	stical Celling Tile				
<u>La</u> y	ver Detail		<u>Fiber</u>	%	
Layer # 1 White	Flakes	Paint			
			None	0	
Layer # 2 Brown	Fibrous	lx I Acoustic ceiling		00.00	
Non-Fibrous Components; Sample Comments:	Binder		Cellulose	80-90	
Sample Number: B-	-2-B09	Lab IL): 45945	· ,	ACM? □
Sample Type: Rooli	ng Felt				
Layer # 1 Black	e <u>r Detail</u> Fibrous	Roofing felt	<u>Fiber</u>	%	
			Cellulose	80-90	
Non-Fibrous Components;	Tar/blumen			•	
Sample Comments:					

Project ID Project Name 7-417-000764 7-417-00076		Name 7-000764_4/	72 5
Sample Number: B-2-B10 Sample Type: Rolled Roofing Male	<i>Lab ID</i> : 45946		ACM? □
<u>Layer Detail</u> Layer # 1 Brown Granular	<u>Fiber</u> Rolled roof	%	
	Cellulose	40-50	
Non-Fibrous Components; Tat/bilume Sample Comments:	Glass fiber	10-20	
Sample Number: B-2-B11 Sample Type: Bluminous Roof Shi	Lab ID: 45947		ACM? □
Layer # 1 Green Granular	<i>Fiber</i> Roof shingle	%	
	Cellulose	40-50	
Non-Fibrous Components; Tar/bilumer Sample Comments:	Glass fiber	20-30	
Sample Number: B-2-B12 Sample Type: Insulation, Loose FIII	Lab ID: 45948		ACM? □
Layer Detail Layer # 1 Gray Fibrous	<i>Fiber</i> Blown-in insulation	%	
	Cellulose	70-80	
	Mineral wool	<1	
Nun-Fibrous Cumponents; Binder Sample Comments:	•		

. . . . - . - . -

	Project Name 7-417-000764	l		ng Name 417-000764_4/25	5	
Sample Number: B	-2-B13	Lab ID:	45949	,	ACM?	
Sample Type: Insu	lation, Loose Fill					
<u>La</u>	yer Detail		<u>Fiber</u>	%		
Layer# 1 Gray	Fibrous	Blown-in insulation				
		(Cellulose	80-90		
Non-Fibrous Components;	Binder					
Sample Comments:						
Sample Number: B	-2-B14	Lab ID:	45950		ACM?	
Sample Type: Insul	ation, Loose Fill					
<u>La</u>	yer Detail		Fiber	%		
Layer # 1 Gray	Fibrous	Blown-in insulation				
		C	Cellulose	80-90		
Non-Fibrous Components;	Binder					
Sample Comments:						
Sample Number: B	-2-B15	Lab ID:	45951		ACM?	П
Sample Type: Acou	stical Ceiling Tile					
<u>La</u> y	ver Detail		Fiber	%		
Layer # 1 White	Flakes	Paint				
			None	0		
Layer # 2 Brown	Fibrous 1	x I Acoustic ceiling til	е			
		C	ellulose	80-90		
Layer # 3 Gray	Fibrous	Debris				
		C	ellulose	70-80		
Non-Fibrous Components;	Binder					
Sample Comments:						

=	Project Name 7-417-000764		Building 7-4]	Name 17-000764_4	/25
Sample Number: H	B-2-B16	Lab	ID: 45952		ACM? □
Sample Type: Plas	ster Wall Texture				
La	yer Detail		<u>Fiber</u>	%	
Layer # 1 White	Flakes	Paint			
			None	0	
Layer # 2 White	Powder	Texture			
1 # 2 D	F**1	D11	Cellulose	1-2	
Layer # 3 Brown	Fibrous	Backing	Cellulose	80-90	
Layer# 4 White	Clumpy	Wall board	Cellulose	6U-9U	
	.,		Cellulose	1-2	
			Glass fiber	2-5	•
Non-Fibrous Components;	Powder, binder				
Sample Comments:					
Sample Number: B	-2-B17	Lab I	D : 45969		ACM? □
Sample Type: Plas	ter Wall Texture				
<u>La</u>	<u>yer Detail</u>		<u>Fiber</u>	%	
Layer # 1 White	Flakes	Paint			
			None	0	
Layer # 2 White	Powder	Texture		_	
Layer # 3 Brown	Fibrous	Backing	None	O	
Layer # 5 Diowii	Linioas	Dacking	Cellulose	80-90	
Layer# 4 White	Clumpy	Wall board	00/11/030	00 70	
			Cellulose	1-2	
			Glass fiber	<l< td=""><td></td></l<>	
Non-Fibrous Components:	Powder, binder				
Sample Comments:					

-	Project Name 7-417-000764		Building 7-41	Name 17-000764_4	25
Sample Number: E Sample Type: Viny	3-2-B18 Vi Sheel Flooring	Lab I	D: 45970		ACM? ☑
<u>La</u> Layer# 1 Black	<u>yer Detail</u> Linoleum	9x9 floor tile	<u>Fiber</u>	%	
			Cellulose	10-20	
			Chrysotile	2-5	
Layer# 2 Black	Fibrous	Backing			
Layer# 3 Black	Powder	Floor filler	Cellulose	10-20	
Non-Fibrous Components; Sample Comments:	Vinyl, binder		None	0	
Sample Number: B	-2-B19	Lab II	D: 45971		ACM? □
Sample Type: Floor	Tile and Maslic				ACM;
Layer # 1 Gray	<u>ver Detail</u> Hard Tile	Floor tile	<u>Fiber</u>	%	
Layer # 2 White	Powder	Floor filler	Cellulose	2-5	
Layer # 3 Brown	Clumpy	Mastic	Cellulose	5-10	
Non-Fibruus Components;	Vinyl, binder		None	0	
Sample Comments:					

LIVIERVIU

Project ID 7-417-000764	Project Name 7-417-000764		Buildin 7-4	g Name 17-000764_4	/25
Sample Number:	B-2-B20	Lab 1	D: 45972		ACM?
Sample Type: Jo	int Compound				
<u>I</u>	ayer Detail		<u>Fiber</u>	%	
Layer # 1 White	Flakes	Paint			
Layer# 2 Tan	Powder	Texture	None	0	
Layer# 3 White	Powder	Texture	Cellulose	1-2	
Layer# 4 White	Fibrous	Backing	None	0	
		_	Cellulose	80-90	
Layer # 5 White	Powder .	Joint compound			
Layer # 6 Brown	Fibrous	Backing	Cellulose	2-5	
Layer # 7 White	Clumpy	Wall board	Cellulose	80-90	
Non-Fibrous Components			Cellulose	1-2	
Sample Comments:	; Powder, binder				
Sample Number:]	B-2-B21	Lab II	D: 45973		
Sample Type: Plas	ster Walls and Celling				
La	iyer Detail		<u>Fiber</u>	%	
Layer # 1 Beige	Flakes	Paint	<u>-</u>		
Layer # 2 White	Powder	Texture	None	0	
			None	0	
Non-Fibrous Components; Sample Comments:	Powder, binder				•
dompte Comments:					

Project ID 7-417-000764	Project Name 7-417-000764		Building 7-4	, Name 17-000764_4	/25
Sample Number:	B-2-B22	Lab I	D: 45974		ACM? □
Sample Type: Jo	int Compound				
<u>I</u>	ayer Detail		<u>Fiber</u>	%	
Layer # 1 Brown	Flakes	Paint			
			None	0	
Layer# 2 White	Powder	Texture			
			Cellulose	5-10	
Invar# 3 Prows	Eibraus	T: L L	Chrysotile	Trace	
Layer # 3 Brown	Fibrous	Fiberboard	Cellulose	80.00	
Non-Fibrous Components	; Binder	•	Centrose	80-90	
Sample Comments: Poir	nt counted 0/400 = 0%				
Sample Number:	B-2-B23	Lab I	D: 45975		ACM? □
Sample Type: Ele	ctrical Wiring Insulati	on			
\underline{L}	ayer Detail		<u>Fiber</u>	%	
Layer # Black	Rubbery	Wire insulation	· .		
			None	0	
Layer # 2 Brown	Fibrous	Wire insulation			
Non-Fibrous Components	: Vinyl, binder		Cellulose	80-90	
Sample Comments:	Yalyi, Dinder				
Sample Number:]	B-2-B24	Lab II	D: 45976		ACM? □
Sample Type: Buil	iding Insulation				
<u>La</u>	iyer Detail		<u>Fiber</u>	%	
Layer# 1 Black	Fibrous	Siding felt			
			Cellulose	80-90	
Von-Fibrous Components;	Binder				
omple Comments:			•	,	
				-n:	
Friday, May 04, 2007			AMEC Repo	rt ID: 1489	

-	roject Name -417-000764		Building 7-41	Name 7-000764_4	/25
Sample Number: B. Sample Type: Roller	2-B25 I Rooling Malerial	Lab II): 45977		ACM? □
<u>Lay</u> Layer# I Brown	e <u>r Detail</u> Granular	Rolled roof	<u>Fiber</u>	%	
			Cellulose	50-60	
Non-Fibrous Components; Sample Comments:	Tar/bilumen		Glass fiber	10-20	
Sample Number: B-Sample Type: Roofin		Lab ID	: 45988		ACM? □
Layer # I Black	e <i>r Detail</i> Fibrous	Tar felt paper	<u>Fiber</u>	%	
Non-Fibrous Components; Sample Comments:	Tar/bitumen, bin	der	Cellulose	80-90	
Sample Number: B-2 Sample Type: Roolin		Lab ID	45989		ACM? □
Layer# 1 Black	<i>r Detail</i> Fibrous	Tar felt paper	<u>Fiber</u>	%	
Non-Fibrous Components; Sample Comments:	Tar/bllumen, bind	der	Cellulose	80-90	

Project ID 7-417-000764	Project Name 7-417-000764	Building Name 7-417-000764_4/25				
Sample Number: B-2-B28 Sample Type: Roofing Felt		Lab ID	**************		ACM? □	
	<i>Layer Detail</i> Fibrous	Tar felt paper	<u>Fiber</u>	%		
Layer # 1 Black	Fibrous	Lat test haber	Cellulosc	80-90		
Non-Fibrous Component Sample Comments:	s; Tar/bitumen, bir	nder				

Analytical Notes

Priscilla Acuna, Approved Signatory

5/4/07 Date 5/4/07

Asbestos analysis was performed by polarized light microscopy (PLM), EPA 600/R-93/116 Method. The following fibrous minerals may be usbestos fibers: Chrysotile, amosite, crocidolite, tremolite/actinolite, and anthophylite. Small diameter fibers such as those found in vinyl floor tile, may not be detected by PLM. Interference with the detection of asbestos may also be caused by some material binders. Semiquantitative analysis of these materials by TEM or some other more sunsitive method is recommended for low percentage or inconclusive results. This report pertains only to the samples listed on the report. Report considered valid when signed by a NVLAP approved signatory. This report may not be used for product endorsement by NVLAP or any other government agency. Partial report reproduction must have consent of AMEC.

AMEC Report ID: 1489

Friday, May 04, 2007

Page 12 of 12



1405 West Auto Drive Tempe, Arizona 85284-1016

ASBESTOS CHAIN OF CUSTODY

(PLM Analysis)

Phone: 480-940-2320 Fax: 480-785-0970 Turnaround Time www.amec.com Client (submitted by): Same Day 1-2 Days 3-5 Days EXYKS NV Other Single Layer Protocol Analyze All Samples Analyze Until 1st Positive City, State, Zip: Results Attention To/Project Manager: DAN SwigeNSKi Spanks とく 8 Q 4 3 4 Sampled By (print): Phone: ANDREW D. SATO Sampled by (signature) Fax: Greden Number of Samples: Date Submitted: F1-53-7 Job Number/Project Name: Special Instructions: ナーム・チ・ひかの そしり ALL SAMPLES COLLECTED ON 4/19/07 LOCATION GUANTITY Sample Number | LOCATION MAP FOR ALL SAMPLE Sample Number | Location and Sample Description LOCATIONS Sample-Time Sample Date 4 800'2 KITCHEN 1) B-2-B01 SHEETROCK, AND TOWNT COMP. AND TEXTUD KITCHEN WALL TEXTURE 2) B-2-B02 KITCHEN 3)8-2-897 WALL TEXTUES 300' GREY) KETCHEN 4)8-2-804 FLOOKITLE AND MASTE 800'Z FLOOR TILE MASTIE BASEMENT 5) B-2-B05 80'2 PHASTER AND SKIM CORT AND COMPOUND BASEMENT BEAM BASEMENT AND KETCHEN 6) B-Z-BOG 900.2 7) B-2-BOT CEILINGPLASTER AND SKIEM CORT 700-2 8) B-2-B08 I'X I ACOUSTIC CELLING TILE BASEMENT 4:000-2 MIE, KOOF PITCHED MND SOUTH ROOFS PITCHED AND SOUTH ROOF 9) 8-2-1309 ROOFING FELT A BOVE KITCHEN 4,000 , 2 10) 8-2-810 ROLLED ROOFING (BEN OVER GRUSHING 4,000 12 11) g- 2-Bu GREEN SHINGLES 7,000 200, 2,20 12) B-2-B12 BLOWN-IN CELLING INSULATION 13) B-R-B13 "DITIO" 14) B-2-B14 *"מזר*דש" 2,20012 I'K' ACOUSTED OFFITAGTILE 15) B-2-B15 THEATER 16) 5-2-816 SHEETROCK AHD WALL TEXTURE THEATER "οππο" 17) 8-2-817 350 18)8-2-818 BLK 9 X9" PATTERN SHEET FLOORING (LIND) NE. ROOMS 8012 LAPTES RIA 9" X9" FLOOK TILE (GREY) + MASTIC 19) B-2-B19 500'2 20)8-2-B20 SHEETROCK AND JOINT COMPOUND AND TEXTURE N.W. RMS Time: 1)Relinquished By: Date: Date: Time: 2) Received By: 12116 423.4 Chroner V. 4/23/07 12:16 PM 4) Received By: Date: Time: 3) Relinquished By: Date: Time: unda anes 4:00D



ASBESTOS CHAIN OF CUSTODY (PLM Analysis)

1405 West Auto Drive Tempe, Arizona 85284-1016 Phone: 480-940-2320 Fax: 480-785-0970 www.amec.com

www.amec.com			Turnaround Time			
Client (submitted by):			☐ Same Day	☐ 1-2 D	avs	
AMEC-	Procker	مریا ا	3-5 Days			
[A J J		1 1	Days C C			
780 V. 279 Z	مدلم لميده		Analyze All Samples	☐ Single Le	yer Protocol	
+810,274	21MA 2510.	9	☐ Analyze	Until 1st Positive		
City, State, Zip:		1 1	Results Attention To/Projec	t Manager:	-	
2 banges b	in Run.	34				
Phone:			Sampled By (print):			
3-775-3	71-237	.57	ANDKEW D SATO			
Fax:			Sampled by (signature):	5		
7-75-33	1-415	ן כ	Date Submitted:	Number of Sai	mples:	
Job Number/Project Name	B.:		21.23.07	Z /-		
7.417. E			Special Instructions:			
7 7 7	11700					
•		Ų		LOCATION	QUAWATY	
Sample Number	4-ocation an	d Samp	le Description	Sample Date	Sample Time	
1) B-2-B21 WALL AND CEL			NG TEXTURE	MENERM	- 500'2	
			ed and joint eomyound	57716E	1,200'2	
3) B-2-B23	B-2-B23 WIRE INSU			STRGE REEA	NUTHTEER	
4) 8-1-824 EXTENTOR SEP			NG FELT	EXTERTOR WALLS	4,500	
5) B-2-825 ROLLED ROOFS			VG	NORTH ROOFS	1,000	
6)						
7)						
8)						
9) 10)						
11)						
12)						
13)						
14)						
15)	i					
16)					·	
17)			, <u> </u>			
18)			- La transfer to the second se	•		
19)						
20)						
				T =	I-m:	
1) Relinquished By:	Date: Tin		2) Received By:	Date:	Time:	
Growth Salo		2:16 PA	4) Received By	Date:	Time:	
3) Relinquished By:	Date: Tim	ic.	The convention	4/25/07	45000	



ASBESTOS CHAIN OF CUSTODY (PLM Analysis)

1405 West Auto Drive Ten	npe, Arizo	na 85284-101	6		•			
Phone: 480-940-2320 Fax: 480-785-0970 www.amec.com			. [Turnaround Time				
Client (submitted by):				П	Same Day	□ 1-2 I	Dave	
,				Ē	3-5 Days		r	
Address:			$\dashv \downarrow$		2-2 Days		· k	
12000				☐ Analyze All Samples ☐ Single Layer Protocol				
City, State, Zip:				Analyze Until 1st Positive Results Attention To/Project Manager:				
		•	- '	Results A	tendon Toleroje	it Manager:		
Phone:				Sampled By (print):				
					W D SA	70		
Fax:					y (signature):	J-17		
			1 -	Date Subr		Number of Sa	implan:	
Job Number/Project Nam	ne:		'	Daic anot	inticu.	Number of Sa	impies.	
JOD HOMBENT TOJECT HAME.				Special Instructions:				
			—	<u>, </u>				
				SAMPLES COLLECTED 4129			4-129	
ample Number		Location and				Sample Date	Sample Tope	
) 6 - 206						FOR SAMPLEL		
) B-2-826	TAK				TH-THEATER	FLOORING		
		" P.T. 770						
) <u>8-2-820</u>			` p <u>T</u> -770	2			<u> </u>	
3							-	
7	-	-}						
5)						-		
2)		- 						
0)		 						
1)		1						
2) 3)		1				· · · · · · · · · · · · · · · · · · ·		
4)								
5)	.	<u> </u>						
6)		t						
8)								
7) 8) 9)					•			
.0)								
Relinquished By:	Date: 5/1/0	7 14:	52	200		Days: 5/4/07	Time: 1040	
) Relinquished By:	Date:	Time		4) Rece	ived By:	Date:	Time:	